



Specifications:

<b>Temp.</b>	<b>Indoor</b>	<b>0 - 50 °C (32-122 °F) Accuracy: ±1.0 °C Resolution: 0.1 °C</b>
	<b>Outdoor</b>	<b>-20~70°C (-4 ~ 120°F) Accuracy: ±1.0 °C Resolution: 0.1 °C</b>
<b>Humidity</b>	<b>30% ~ 90%RH Accuracy: ±5% Resolution: 1%RH</b>	

**TH804 Mini Digital Thermometer with Humidity & Clock**

**Features**

- \* LCD Display showing indoor Temp, humidity and time at the same time ideal for home, office, school
- \* Recording MAX / MIN Temperature & Humidity value automatically
- \* Selectable temperature unit: °C/°F (by pushing switch at back side)
- \* 2 modes for time showing: 12H or 24H
- \* With calendar, clock and alarm function
- \* With back stand
- \* Comfortable degree symbol showing: COMFORT, WET, DRY

<b>Temp.</b>	<b>0 - 50 °C (32-122 °F) Accuracy: ±1.0 °C Resolution: 0.1 °C</b>
<b>Humidity</b>	<b>30% - 90%RH Accuracy ±5% Resolution: 1%RH</b>



TH804

**Humidity&temperature Meter**

Specifications	AR-817	AR-827	AR-837	AR-847
Temperature Range	-10°C-50°C	-10°C-50°C	-10°C-50°C	-10°C-50°C 20°C-1000°C(K-TYPE)
Humidity Range	10%RH-99%RH	10%RH-99%RH	5%RH-98%RH	
Accuracy Of Temperature	±1°C ±1.8°F	±1°C ±1.8°F	±1°C ±1.8°F	±1°C ±1.8°F
Accuracy Of Humidity	±3%(30-99%) ±5%(10-30%)	±3%(30-99%) ±5%(10-30%)	±3%(30-95%) ±5%(10-30%)	±3%(30-95%) ±5%(10-30%)
°C/°F Selection	✓	✓	✓	✓
Auto/Manual Power Shut Off			✓	
Low Battery Indication	✓	✓	✓	✓
Data Hold	—	✓	✓	
Temperature Resolution	0.1°C	0.1°C	0.1°C	0.1°C
Humidity Resolution			0.1%RH	
Sampling Rate	2 times/sec	2 times/sec	2.5 times/sec	2.5 times/sec
Max / Min. Function	—	—	✓	
K-type Thermocouple Temperature Measuring	—	—	—	✓
Large LCD Temperature & Humidity Dual Display	—	—	✓	✓



AR847

AR827

**Digital temperature Meter**

**DT801: Digital Instant-Read Thermometer**

**Function:**

- \* Being instant and accurate reading, the digital instant-read thermometer is not only;
- \* Widely used for cooking, barbecue, milk, drink, water, oil, air, etc., but also for Industry or laboratory;
- \* Memory of last measuring;
- \* °C/°F unit changing switch;
- \* Temperature hold;
- \* Low battery and Overload indicators;
- \* 15 minutes auto power-off;
- \* Sampling rate: 2.5 second.

<b>Measurement Range</b>	<b>-50°C~300°C (-58°F~572°F)</b>
<b>Accuracy</b>	<b>0-80°C: ±1°C; Other: ±5°C</b>
<b>Resolution</b>	<b>0.1°C (0.1°F)</b>



DT801