



## Light Meters

### LX801: Pocket Light Meter

Measures up to 50,000Lux for basic lighting applications

Features:

- \* Easy to operate Lux light meter with 3 range
- \* Convenient pocket size design
- \* Data Hold

<b>Lux Range</b>	2000,20000,50000Lux
<b>Basic Accuracy</b>	± 4% rdg
<b>Max.Resolution</b>	1Lux



LX801



LX802

### LX802: Heavy Duty Light Meter, Digital display of light in Foot-candles or LUX

Features:

- \* Wide range to 20,000 Foot-Candles or Lux with high resolution to 0.01 FC/Lux
- \* Peak mode captures highest reading
- \* Data hold and peak hold

<b>Lux Range</b>	200,2000,20000,20000Lux
<b>Fc Range</b>	20,200,2000,20000Fc
<b>Basic Accuracy</b>	± (3%rdg+10)
<b>Max.Resolution</b>	0.1Fc/1Lux



AR823

### AR823: Light Meter

Digital and Analog display of light in Foot-candles or LUX

Features:

- \* Relative mode indicate change in light levels
- \* Peak mode captures highest reading
- \* Min/Max and Data Hold
- \* Large LCD display with analog bargraph
- \* Backlight for readings in low light levels

<b>Lux Range</b>	100,000Lux
<b>Fc Range</b>	10,000Fc
<b>Basic Accuracy</b>	± (3%rdg+10)
<b>Max.Resolution</b>	0.01Fc/Lux



WM801

## Insulation Tester

### WM801 Wood Moisture Meter, Pocket Size Moisture Detector

- \* This meter measures moisture content of any lumber, including fabricated woods, hardwoods, and soft woods.
- \* Accurately measures from 6% to 24% moisture content in all lumber.
- \* To use the meter simply insert the meter 2 pins into the wood and press the on/off switch.
- \* A bright LED will give you an instant accurate moisture content reading.
- \* Includes a 9-volt battery.

### ST57A: Non-Invasive Measurement

With virtually no surface damage simply lay meter on surface to measure moisture content

Features:

- \* Non-destructive moisture measurement of all kind of wood.
- \* Can be measured in the depth of 50mm.
- \* Easy to read LCD screen
- \* Completely portable

Specifications:

- \* Measuring way: electromagnetic wave introduction (The switch-on with automatic calibration)
- \* Measuring range: 3%~40% (the depth of measuring: 0~50mm)
- \* Resolution: 0.1% moisture content
- \* Accuracy: ±2%



ST-57A